



# DRCC DEHUMIDIFIER



- w+ Suitable for all installations
- w+ Available models: ductable
- w+ Galvanised metal bodywork
- w+ Ideal for SPA or indoor pool

- w+ CE certification
- w+ Electric auxiliary heating
- w+ R134a gas for DRCC 33 and DRC 66
- w+ R410a gas for DRCC 100



## DRCC DEHUMIDIFIER

Can be ducted thanks to its installation kits



### SPECIFICATIONS

PRODUCT	DRCC 33 *	DRC 66 *	DRCC 100 *
Capacity	1.37 L/h	2.83 L/h	4.16 L/h
Extraction per day	33 L	68 L	100 L
Air flow	320 m <sup>3</sup> /h	560 m <sup>3</sup> /h	1000 m <sup>3</sup> /h
Sound volume	38 dB	40 dB	53 dB
Power	230 V	230 V	230 V
Rated current (35°C - 95% HR)	3 A	4.9 A	7.2 A
Max. power consumption (32°C - 95% HR)	460 kW	890 kW	1830 kW
Relative humidity	45 - 98% HR	40 - 95% HR	50 - 98% HR
Temperature	-10°C - 33°C	-10°C - 33°C	-10°C - 33°C
Gas	R134a	R134a	R410a
Electricity supply included		Optional on request	
Diameter condensation plug	16 mm	16 mm	16 mm
Unit size (l / L / h)	652 * 260 * 662 mm	936 * 309 * 708 mm	1172 * 871 * 315 mm
Box size (l / L / h)	830 * 780 * 305 mm	1005 * 765 * 360 mm	1425 * 892 * 400 mm
Net weight	33 kg	52 kg	81 kg
Brut weight	37 kg	56 kg	85 kg
Warranty all parts	2 years	2 years	2 years

\* Test performed at 30°C air temperature and 80% humidity

\* Operating limit :

- Temperature: 10°C - 32°C

- Relative humidity : 40% - 90%.

### ACCESSORIES

- Optional electric auxiliary heater
- Optional room and galvanised thermostat and hygostat
- User manual