

WD DEHUMIDIFIER



- Design - Tempered glass front
- Easy installation with the included wall bracket
- Intuitif touch - Digital LED touch screen
- Ideal for SPA ou indoor pool
- Complies with FPP standards
- 2 kW electric space heater
- R32 ecological gas
- CE certificate

wpool.fr

WD DEHUMIDIFIER

DIGITAL LED TOUCH SCREEN
ON TEMPERED GLASS FRONT



SPECIFICATIONS

PRODUCT	WD2.2E *	WD3.5E *	WD4.5E *
Capacity	2.2 L/h	3.5 L/h	4.5 L/h
Extraction per day	53 L	84 L	108 L
Air flow	525 m^3/h	750 m^3/h	1030 m^3/h
Sound volume	44 dB	46 dB	48 dB
Sound volume (distance)	1 m	1 m	1 m
Power	240 V / 50 Hz	240 V / 50 Hz	240 V / 50 Hz
Power consumption	0.93 kW	1.13 kW	1.97 kW
Rated current	4.1 A	5.0 A	8.7 A
Max. power	1.02 kW	1.32 kW	2.28 kW
Max. power consumption	4.3 A	5.85 A	10 A
Max. current absorbed	13.6 A	15 A	19.5 A
Relative humidity	40-90 %RH	40-90 %RH	40-90 %RH
Temperature	10-32°C	10-32°C	10-32°C
Gas	R 32	R 32	R 32
Electricity included	2 kW	2 kW	2 kW
Diameter condensation plug	16 mm	16 mm	16 mm
Unit size	1300 * 615 * 209 mm	1479 * 615 * 209 mm	1690 * 647 * 207 mm
Box size (l/L/h)	1343 * 790 * 248 mm	1543 * 790 * 248 mm	1743 * 790 * 248 mm
Net weight	63 kg	77 kg	82 kg
Brut weight	73 kg	89 kg	94 kg
Warranty all parts	2 years	2 years	2 years

* Place the dehumidifier more than 3.5 meters from the water source and more than 30 cm from the ground.

* Electric auxiliary heating suitable for interior spaces of up to 15m^2.

* Test performed at 30°C air temperature and 80% humidity.

* Operating limit :
  - Temperature: 10°C - 32°C
  - Relative humidity : 40% - 90%

These models are available with a hot water auxiliary heater on order only. Please note that longer delivery times may apply.

ACCESSORIES

- Wall bracket supplied
- Condensate drain pipe
- Removable feet
- User manual